

MIDI SIDE VIEW 13X12MM LED NEON FLEX, COOL WHITE 6000K, 24V, IP67 (10M KIT)


| SKU: NEONSIDE1312/10MKIT-CW

tagra®

 tagra-lighting.co.uk

 0161 442 1180

 orders@tagra-lighting.co.uk



FEATURES & BENEFITS

- Featuring a 90 CRI spot free high lumen output, this revolutionary neon flex can be recessed or surface mounted making it a complete, highly versatile systematic installation solution
- High quality, high brightness
- Suitable for indoor and outdoor use
- Salt Water Resistant
Solvent Resistant
UV Resistant
Flame Resistant




TECHNICAL INFORMATION

Neon Specifications

SKU Code	NEONSIDE1312/10MKIT-CW
Voltage	24V
Watts p/M	10.6W p/M
Colour	Cool White
Colour Temp	6000K
Lumens p/M	670LM
Min Bend Radius	60mm
CRI	90
Dimensions	13mm x 12mm x 10000mm
IP Rating	IP67
IK Rating	IK08
Cut Points	Every 50mm
Operating Temp	-20°C to +45°C
Lifespan	Up to 36000 Hours
Certification	CE, RoHs, UL, Reach
Guarantee	3 Years

Driver Requirements

1 Metre	> 12W
2 Metres	> 24W
3 Metres	> 36W
4 Metres	> 48W
5 Metres	> 61W
6 Metres	> 72W
7 Metres	> 84W
8 Metres	> 98W
9 Metres	> 110W
10 Metres	> 125W



DESCRIPTION

Introducing our IP67 Silicone Neon Flex, at only 13 x 12mm and featuring a 90 CRI spot free high lumen output, this revolutionary neon flex can be recessed or surface mounted making it a complete, highly versatile systematic installation solution.

Also featuring resistance to saline solutions, acid & alkali, corrosive gases, fire and UV, this Neon Flex is a perfect lighting solution for both heavy duty and display lighting requirements. These features make this Neon Flex suitable for installations on yachts, super yachts, facade lighting, indoor and outdoor projects.

Making use of a vertical bend and side light emittance it can be easily moulded and shaped to your requirements and is a more up to date modern solution to PVC neon.

This 10 metre kit includes

A 10 metre reel of silicone neon flex with a 1 metre DC 5.5 female connector power feed at each end, 1 set of end caps, 1 silicone glue tube, 2 solder-free connectors and PC mounting clips. **The cable length can be extended at each end to your specification. Please get in touch if you would like a quote for this service.**

GALLERY

