SIDE VIEW 13X12MM LED NEON FLEX, NEUTRAL WHITE 4000K, 48V, IP67 (50M REEL)

| SKU: NEONSIDE1312/50M-NW



IP67 | 4000 K | 48V | Dimmable | 90 CRI | c UL us E498657 | Reach | CE | RoHs | 3YR Guarantee

TECHNICAL INFORMATION

Neon Specifications

SKU Code	NEONSIDE1312/50M-NW
Voltage	48V
Watts p/M	5.3W p/M
Colour	Neutral White
Colour Temp	4000K
Lumens p/M	350LM
Min Bend Radius	60mm
CRI	90
Dimensions	13mm x 12mm x 50000mm
IP Rating	IP67
IK Rating	IK08
Cut Points	Every 100mm
Operating Temp	-20°C to +45°C
Lifespan	Up to 36000 Hours
Certification	CE, RoHs, UL, Reach
Guarantee	3 Years

Driver Requirements

1 Metre	> 6W
2 Metres	> 12W
3 Metres	> 18W
4 Metres	> 24W
5 Metres	> 30W
6 Metres	> 36W
7 Metres	> 42W
8 Metres	> 48W
9 Metres	> 54W
10 Metres	> 60W



tagra-lighting.co.uk

0161 442 1180

orders@tagra-lighting.co.uk

FEATURES & BENEFITS

- Featuring a 90 CRI spot free high lumen output, this revolutionary neon flex can be recessed or surface mounted making it a complete, highly versatile systematic installation solution
- High quality, high brightness
- Suitable for indoor and outdoor use
- Salt Water Resistant
  Solvent Resistant
  UV Resistant
  Flame Resistant

DESCRIPTION

Introducing our IP67 Silicone Neon Flex, at only 13 x 12mm and featuring a 90 CRI spot free high lumen output, this revolutionary neon flex can be recessed or surface mounted making it a complete, highly versatile systematic installation solution.

Also featuring resistance to saline solutions, acid & alkali, corrosive gases, fire and UV, this Neon Flex is a perfect lighting solution for both heavy duty and display lighting requirements. These features make this Neon Flex suitable for installations on yatchs, super yatchs, facade lighting, indoor and outdoor projects.

Making use of a vertical bend and side light emittance it can be easily moulded and shaped to your requirements and is a more up to date modern solution to PVC neon.

Our 50 metre reels of Neon Flex are supplied in a continuous 50 metre length

GALLERY